

SPECIFICATIONS

SPECIFICATION		RWL928
Dimensions	Overall length (mm)	5650
	Overall height (mm)	2750
	Tire outer width (mm)	1800
	Outer width of bucket (mm)	1850
	Unloading height (mm)	3200
	Unloading distance (mm)	700
	Maximum height on the bucket (mm)	4350
	Bucket lower pin shaft height	3750
	Front turning radius (mm)	5200
	Rear turning radius (mm)	4350
	Minimum ground clearance (mm)	240
	Wheel base (mm)	2230
	Track width (mm)	1490
	Front wheel center to hinge (mm)	950
	Steering angle (°)	30
	Collect the bucket angle in place (°)	50
Unloading angle at the highest position (°)	36	
Departure angle (°)	25	
Overall performance	Rated load capacity (kg)	1500
	Whole machine weight (kg)	3400
	Standard bucket size (mm)	1800x920x470
	Standard bucket capacity (m ³)	0.8
	Empty lifting / Unloading time (S)	4.6/3.9
Power performance	Engine	SIDA 490
	Rated power (kW)	42
	Emission	Stage - 2
Transmission	Transmission model	265 (Split body)
	Drive axle model	LG 1.5T (Small wheel side axle)
	Transmission gear	F4 / R4
	Tire model	20.5 - 16
Hydraulic system	Working hydraulic operation mode	Single lever operation
	Working hydraulic system pressure	16
	Steering hydraulic system pressure	8
Brake system	Driving brake form	Air top oil brake
	Parking brake form	Hand brake
Electrical system	Voltage	24

RHINO

RWL928

OPERATING WEIGHT
3400 kg 7495 lb

BUCKET CAPACITY
0.8 m³ 1.04 yd³

LOAD MEIZTER



WHEEL LOADER

RHINO CONSTRUCTION MACHINERY

